

Rotary hammer TE 2-M



Applications

- Everyday hammer drilling in concrete, masonry and natural stone
- 2 gears for optimal drilling speed in steel, wood and plastics using the optional quick-release chuck
- Driving screws using the optional bit holder
- Reverse rotation is useful for removing stuck drill bits

Advantages


- Triple-mode SDS rotary hammer (hammer drilling plus 2 gears for rotary-only drilling)
- Sturdy motor with high load rating for maximum reliability
- Quick-change "TE-C Click" chuck and user-friendly selector switch for high working comfort
- Electronic switch for precise hole-starting
- 360° side handle adjusts easily for preference or for use in tight spaces
- Quick-release chuck for drilling in steel, wood and plastics

Technical data

Working mode	Hammer drilling, Drilling only
Optimum drilling diameter in concrete	4 - 12 mm
Drilling diameter range for hammer drill bits	4 - 22 mm
Single impact energy	1.8 J
Triaxial vibration value for hammer drilling into concrete (ah,HD)¹⁾	13.5 m/s ²
A-weighted emission sound pressure level²⁾	91 dB (A)
Dust removal module	TE DRS-S (optional)
Full hammering frequency	4600 impacts/minute
Dimensions (LxWxH)	360 x 89 x 203 mm
Weight according to EPTA Procedure 01/2003	2.9 kg

¹⁾ according to EN 60745-2-6

²⁾ according to EN 60745



Ordering designation	Package contents	Sales pack quantity	Item number
TE 2-M	1x Rotary hammer TE 2-M 230V GB, 1x Case	1 pc	228117

Please visit our website for the latest item numbers and related products.