

Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Issue date: 27/06/2023 Revision date: 27/06/2023 Supersedes: 22/09/2014 Version: 2.0

SECTION 1: Identification

1.1. GHS Product identifier

Product form Mixture
Name GC 42
UN-No. (ADR) 3150

Product code BU Direct Fastening



1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use For professional use only

Propellant for direct fastening tools.

1.4. Supplier's details

Supplier

Hilti (Philippines) Inc.

2256 Pasong Tamo Extension Edsa, Brgy. Magallanes

PH- 1224 Makati City

Philippinen

T +632 784 7100 - F +63 2 784 7100 customerservice.ph@hilti.com

Department issuing data specification sheet

Hilti AG

Feldkircherstraße 100 FL- 9494 Schaan Liechtenstein T +423 234 2111 df-hse@hilti.com

1.5. Emergency phone number

Emergency number Emergency contact (24 hours per day)

GBK GmbH Global Regulatory Compliance +49 (0)6132-84463

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Flammable gases, Category 1A H220 Expert judgement Gases under pressure : Compressed gas H280 Expert judgement

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS UN)





Signal word (GHS UN)

Hazard statements (GHS UN)

Precautionary statements (GHS UN)

Danger

H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

27/06/2023 PH - en 1/9



Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

P381 - In case of leakage, eliminate all ignition sources.

P403 - Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
isobutane	CAS-No.: 75-28-5	55 - <65	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
propene	CAS-No.: 115-07-1	20 - <30	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
Propane	CAS-No.: 74-98-6	5 - <15	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Full text of H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general Take off immediately all contaminated clothing.

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact Gently wash with plenty of soap and water.

First-aid measures after eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion Immediately consult a doctor/medical service.

4.2. Most important symptoms/effects, acute and delayed

Potential adverse human health effects and

symptoms

No additional information available. No harmful effects are to be expected if used properly. The contained ingredients can be harmful, but they are hermetically enclosed in the article

and can not be released.

The dismantling of the article is prohibited.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media Carbon dioxide. Water spray. Dry powder. Alcohol resistant foam.

Unsuitable extinguishing media Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Explosion hazard Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

Hazardous decomposition products in case of fire On burning: release of (highly) toxic gases/vapours. Thermal decomposition generates :

Carbon dioxide. Carbon monoxide.

27/06/2023 PH - en 2/9



Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

5.3. Special protective actions for fire-fighters

Precautionary measures fire Fight fire remotely due to the risk of explosion.

Firefighting instructions DO NOT fight fire when fire reaches explosives. Evacuate area.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

Self-contained breathing apparatus.

Other information EN 12942. EN 12941.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures Evacuate area. Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures Ventilate spillage area. Evacuate area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment Do not attempt to take action without suitable protective equipment. Breathing apparatus.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up Do not flush with water.

Other information For further information refer to section 8: "Exposure controls/personal protection". For

further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling Do not spray on an open flame or other ignition source. Avoid contact with skin, eyes and

clothing. Do not breathe vapours. Prevent the build-up of electrostatic charge.

Hygiene measures Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

Additional hazards when processed Flammable gas. Do not pierce or burn, even after use. Keep away from heat, hot surfaces,

sparks, open flames and other ignition sources. No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures Proper grounding procedures to avoid static electricity should be followed.

Storage conditions Keep cool. Protect from sunlight. Keep in fireproof place. Store in dry protected location to

prevent any moisture contact.

Incompatible materials Heat sources. Direct sunlight. Sources of ignition.

Heat and ignition sources Keep away from heat and direct sunlight. Keep away from ignition sources.

Information on mixed storage Do not store with DX powder cartridges.

Storage temperature 5-25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

Ensure good ventilation of the work station.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection In case of repeated or prolonged contact wear gloves

27/06/2023 PH - en 3/9



Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	3 (> 60 minutes)	0,12		EN ISO 374

Eye protection Chemical goggles or safety glasses. ISO 16321-1. EN 170

Skin and body protection When using cartridge operated tools, sufficient ear protection must be worn.

Respiratory protection No respiratory protection needed under normal use conditions

Personal protective equipment symbol(s)







8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical stateGasColourColourless.OdourSweet.Odour thresholdNot availableMelting pointNot applicableFreezing pointNot applicableBoiling pointNot available

Flammability Extremely flammable aerosol, Extremely flammable gas.

Lower explosion limit 1.7 vol % Upper explosion limit 11.1 vol % Not applicable Flash point Not available Auto-ignition temperature Decomposition temperature Not available рΗ Not applicable pH solution Not applicable Viscosity, kinematic (calculated value) (40 °C) Not applicable Not available Partition coefficient n-octanol/water (Log Kow) 8300 hPa Vapour pressure Vapour pressure at 50°C Not available

Density 0.6 g/cm³ (DIN 51757)

Relative density

Relative vapour density at 20°C

Solubility

Particle size

Not applicable

Not available

insoluble in water.

Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

Explosive properties Product is not explosive. In use, may form flammable/explosive vapour-air mixture

Gas group Gases under pressure : Compressed gas

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

27/06/2023 PH - en 4/9



Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological informa	tion
11.1. Information on toxicological effects	
Acute toxicity (oral)	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	Not classified (Based on available data, the classification criteria are not met)
isobutane (75-28-5)	
LC50 Inhalation - Rat [ppm]	> 18000 ppm
propene (115-07-1)	
LC50 Inhalation - Rat	> 688 mg/m³
Propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 280000 ppm (literature)
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitisation	Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	Not classified (Based on available data, the classification criteria are not met)
GC 42	
Vaporizer	Container fitted with a sealed spray attachment
Potential adverse human health effects and	No additional information available. No harmful effects are to be expected if used properly.
symptoms	The contained ingredients can be harmful, but they are hermetically enclosed in the article and can not be released.

SECTION 12: Ecological information

12.1. Toxicity	
Ecology - general	Due to the consistency along with the low water solubility of the product a bioavailability is unlikely.
Hazardous to the aquatic environment, short–term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified

The dismantling of the article is prohibited.

27/06/2023 PH - en 5/9



Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

SECTION 13: Disposal considerations

isobutane (75-28-5)	
LC50 - Fish [1]	24.11 – 147.54 mg/l (Quantitative structure-activity relationship (QSAR))
EC50 - Crustacea [1]	7.02 – 69.43 mg/l (Quantitative structure-activity relationship (QSAR))
ErC50 algae	7.71 – 16.5 mg/l (Quantitative structure-activity relationship (QSAR))
propene (115-07-1)	
LC50 - Fish [1]	43.3 mg/l (72 h; Oncorhynchus mykiss (Rainbow trout); Quantitative structure-activity relationship (QSAR))
EC50 - Crustacea [1]	28.2 mg/l (48 h; daphnia; Quantitative structure-activity relationship (QSAR))
EC50 96h - Algae [1]	12.1 mg/l (algae; Quantitative structure-activity relationship (QSAR))
12.2. Persistence and degradability	
GC 42	
Persistence and degradability	No additional information available
isobutane (75-28-5)	
Persistence and degradability	Readily biodegradable.
propene (115-07-1)	
Persistence and degradability	Readily biodegradable in water.
Propane (74-98-6)	
Persistence and degradability	Readily biodegradable in water.
12.3. Bioaccumulative potential	
GC 42	
Bioaccumulative potential	No additional information available
isobutane (75-28-5)	
Partition coefficient n-octanol/water (Log Kow)	1.09 – 2.8 (20 °C)
Bioaccumulative potential	Bioaccumulation unlikely.
propene (115-07-1)	<u>'</u>
Partition coefficient n-octanol/water (Log Pow)	1.77 (20 °C)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Propane (74-98-6)	
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
12.4. Mobility in soil	1
GC 42	
Mobility in soil	No additional information available
12.5. Other adverse effects	
Ozone Other adverse effects Other information	Not classified No additional information available Avoid release to the environment.

13.1. Disposal methods		
Regional legislation (waste)	Disposal must be done according to official regulations.	
27/06/2023	PH - en	6/9



Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Waste treatment methods

Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations

Container under pressure. Do not drill or burn even after use.

Additional information

Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
UN 3150	UN 3150	UN 3150	UN 3150
14.2. UN proper shipping name	e		
HYDROCARBON GAS REFILLS FOR SMALL DEVICES	HYDROCARBON GAS REFILLS FOR SMALL DEVICES	Hydrocarbon gas Refills for small devices	HYDROCARBON GAS REFILLS FOR SMALL DEVICES
Transport document description			
UN 3150 HYDROCARBON GAS REFILLS FOR SMALL DEVICES, 2.1, (D)	UN 3150 HYDROCARBON GAS REFILLS FOR SMALL DEVICES, 2.1	UN 3150 Hydrocarbon gas Refills for small devices, 2.1	UN 3150 HYDROCARBON GAS REFILLS FOR SMALL DEVICES, 2.1
14.3. Transport hazard class(e	s)		
2.1	2.1	2.1	2.1
2	2	2	2
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information availa	able	1	1

14.6. Special precautions for user

Overland transport

6F
0
E0
P209
MP9
2
CV9
S2
D

Transport by sea

runopon by cou	
Limited quantities (IMDG)	0
Excepted quantities (IMDG)	E0
Packing instructions (IMDG)	P003
EmS-No. (Fire)	F-D
EmS-No. (Spillage)	S-U

27/06/2023 PH - en 7/9



Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

Stowage category (IMDG)	В
Stowage and handling (IMDG)	SW2
MFAG-No	115

Air transport

PCA Excepted quantities (IATA)	E0
PCA Limited quantities (IATA)	Forbidden
PCA limited quantity max net quantity (IATA)	Forbidden
PCA packing instructions (IATA)	201
PCA max net quantity (IATA)	1kg
CAO packing instructions (IATA)	201
CAO max net quantity (IATA)	15kg
Special provisions (IATA)	A802
ERG code (IATA)	10L

Rail transport

Classification code (RID)	6F
Limited quantities (RID)	0
Excepted quantities (RID)	E0
Packing instructions (RID)	P209
Mixed packing provisions (RID)	MP9
Transport category (RID)	2
Special provisions for carriage - Loading, unloading	CW9
and handling (RID)	
Colis express (express parcels) (RID)	CE2
Hazard identification number (RID)	23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

SDS Major/Minor	None
Issue date	27/06/2023
Revision date	27/06/2023
Supersedes	22/09/2014

Abbreviations and acronyms CAS-No. - Chemical Abstract Service number

ADN - European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways

ADR - European Agreement concerning the International Carriage of Dangerous Goods by

Road

ATE - Acute Toxicity Estimate

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

DNEL - Derived-No Effect Level
EC50 - Median effective concentration
ED - Endocrine disrupting properties
EC-No. - European Community number

EN - European Standard

IATA - International Air Transport Association
IMDG - International Maritime Dangerous Goods
IOELV - Indicative Occupational Exposure Limit Value

27/06/2023 PH - en 8/9



Safety Data Sheet

according to the United Nations GHS (Rev. 9, 2021)

LC50 - Median lethal concentration

LD50 - Median lethal dose

NOEC - No-Observed Effect Concentration

OECD - Organisation for Economic Co-operation and Development

N.O.S. - Not Otherwise Specified

OEL - Occupational Exposure Limit

PBT - Persistent Bioaccumulative Toxic

PNEC - Predicted No-Effect Concentration

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

SDS - Safety Data Sheet

STP - Sewage treatment plant

TLM - Median Tolerance Limit

TRGS - Technical Rules for Hazardous Substances

VOC - Volatile Organic Compounds

WGK - Water Hazard Class

vPvB - Very Persistent and Very Bioaccumulative

NOAEL - No-Observed Adverse Effect Level

NOAEC - No-Observed Adverse Effect Concentration LOAEL - Lowest Observed Adverse Effect Level

Department issuing data specification sheet.

Training advice

Full text of H-statements:	
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated

SDS UN HILTI

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

27/06/2023 PH - en 9/9