

Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basisIssue date: 11/11/2024Revision date: 11/11/2024Version: 7.22

SECTION 1: Identification			
1.1. GHS Product identifier			
Product form	Article		
Product name	Li-Ion Batteries <100 Wh		
UN-No. (ADR)	3480		
Product code	BU ET&A		
1.2. Other means of identification			
Other means of identification	Hilti B 7/1.5 Li-lon (01), Hilti B 7/2.0 Li-lon (01), Hilti B 7/2.5 Li-lon (01), Hilti B 12/2.6 Li-lon (01), Hilti B 12/4.0 Li-lon (01), Hilti B 12-30 Li-lon (01), Hilti B 12-55 Li-lon (01), Hilti B 14/1.6 Li-lon (01), Hilti B 14/2.6 Li-lon (01), Hilti B 14/3.3 Li-lon (01), Hilti B 18/1.6 Li-lon (01), Hilti B 18/2.6 Li-lon (01), Hilti B 18/2.6 Li-lon (02), Hilti B 18/3.3 Li-lon (01), Hilti B 22/1.6 Li-lon (01), Hilti B 22/2.6 Li-lon (01), Hilti B 22/2.6 Li-lon (02), Hilti B 22/3.0 Li-lon (01), Hilti B 22/3.3 Li-lon (01), Hilti B 22/4.0 Li-lon (01), Hilti B 36/2.4 Li-lon (01), Hilti B 36/2.6 Li-lon (02), Hilti B 144/2.6 Li-lon (01), Hilti B 36/2.6 Li-lon (01), Hilti B 22-55 Li-lon (01), Hilti B 22-85 Li-lon (01), Hilti B 22-100 Li-lon (01)		
1.3. Recommended use of the chemical	and restrictions on use		
Recommended uses and restrictions	For professional use only		
Recommended use	Rechargeable Lithium Ion battery for power tools		
1.4. Supplier's details			
Supplier	Department issuing data specification sheet		
Hilti (Philippines) Inc.	Hilti AG		
2256 Pasong Tamo Extension	Feldkircherstraße 100		
Edsa, Brgy. Magallanes	FL 9494 Schaan		
PH 1224 Makati City	Liechtenstein		
Philippinen	T +423 234 2111		
T +632 784 7100, F +63 2 784 7100	product.compliance-power.tools@hilti.com		
customerservice.ph@hilti.com			
1.5. Emergency phone number			
Emergency number	Emergency CONTACT (24-Hour-Number):		
	GBK GmbH Global Regulatory Compliance		
	+49 (0)6132-84463		
	+632 784 7100		
SECTION 2: Hazard identification			
2.1. Classification of the substance or m			

Classification according to the United Nations GHS

Not classified

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

No labelling applicable



Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification	For the battery chemical materials are stored in a hermetically sealed metal case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.
	It may cause heat generation or electrolyte leakage if battery terminals contact with other metals. Electrolyte is flammable. In case of electrolyte leakage move the battery from fire immediately. However if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery case will be breaked at the extreme, hazardous materials may be released.

Moreover, if heated strongly by a surrounding fire, acrid gas may be emitted.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable ---

Comments	Lithium Ion rechercheable	Lithium Ion rechercheable battery pack:		
		nergy content (Wh)		
	B 7 / 1.5 Li-lon (01)	10,80		
	B 7 / 2.0 Li-lon (01)	14,40		
	B 7 / 2.5 Li-lon (01)	18,00		
	B 12 / 2.6 Li-Ion (01)	28,10		
	B 12 / 4.0 Li-Ion (01)	42,66		
	B 12-30 Li-Ion (01)	27.00 / 28,10		
	B 12-55 Li-Ion (01)	54,00		
	B 14 / 1.6 Li-Ion (01)	23,00		
	B 14 / 2.6 Li-Ion (01)	36,00		
	B 14 / 3.3 Li-Ion (01)	48,00		
	B 14 / 5.2 Li-Ion (01)	73,40		
	B 18 / 1.6 Li-Ion (01)	34,60		
	B 18 / 2.6 Li-Ion (01)	56,20		
	B 18 / 2.6 Li-Ion (02)	56,20		
	B 18 / 3.3 Li-Ion (01)	71,30		
	B 22 / 1.6 Li-Ion (01)	34,60		
	B 22 / 2.6 Li-Ion (01)	56,20		
	B 22 / 2.6 Li-Ion (02)	56,20		
	B 22 / 3.0 Li-Ion (01)	64,80		
	B 22 / 3.3 Li-Ion (01)	71,30		
	B 22 / 4.0 Li-lon (01)	86,40		
	B 36 / 2.6 Li-lon (01)	93,60		
	B 36 / 2.6 Li-Ion (02)	93,60		
	B 144 / 2.6 Li-Ion (01)	37,44		
	B 22-55 Li-lon (01)	54,00		
	B 22-85 Li-lon (01)	85,32		
	B 22-100 Li-lon (01)	97,2		
	This product contains a p	ositive electrode (Lithium cobalt oxide (CAS-No. 12190-79-3)), a		
	negative electrode (graph	negative electrode (graphite (CAS-No. 7782-42-5)) and electrolyte (ethylene		
	carbonate(CAS-No. 96-49	carbonate(CAS-No. 96-49-1), diethyl carbonate (CAS-No. 105-58-8) and lithium		
	hexafluorophosphate (CA	hexafluorophosphate (CAS-No. 21324-40-3)).		
	The physical form of the p	product, however, precludes exposure to workers under normal		
	conditions of use.			
11/11/2024	PH - en			



Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

This mixture does not contain any substances to be mentioned according to the applicable regulations

SECTION 4: First-aid measures			
4.1. Description of necessary first-aid measures			
First-aid measures general	If the electrolyte is leaking out of the battery pack, the following measures have to be taken.		
First-aid measures after inhalation	Allow affected person to breathe fresh air. Allow the victim to rest.		
First-aid measures after skin contact	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.		
First-aid measures after eye contact	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.		
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.		
4.2. Most important symptoms/effects, acute and delayed			
Symptoms/effects	Not expected to present a significant hazard under anticipated conditions of normal use.		
Potential adverse human health effects and symptoms	This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following effects are known when getting into contact: Irritation: severely irritant to eyes. Irritation: may cause irritation to the respiratory system.		

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures			
5.1. Suitable extinguishing media			
Suitable extinguishing media	Cool batteries and accumulators with water jet. In case of fire in the surroundings: Use extinguishing agent suitable for surrounding fire.		
Unsuitable extinguishing media	No additional information available.		
5.2. Specific hazards arising from the chemical			
Hazardous decomposition products in case of fire	Formation of toxic gases is possible during heating or in case of fire.		
5.3. Special protective actions for fire-fighters			
Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.		
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.		
SECTION 6: Accidental release mea	sures		
6.1. Personal precautions, protective equipment and emergency procedures			
General measures	No flames, no sparks. Eliminate all sources of ignition. Isolate from fire, if possible, without unnecessary risk.		

6.1.1. For non-emergency personnel	
Protective equipment Emergency procedures	Wear protective gloves. protective clothing. Safety goggles. Gas mask. Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment Emergency procedures	Equip cleanup crew with proper protection. Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Prevent entry to sewers and public waters. Notiny autionities in liquid enters sewers of public waters.			
6.3. Methods and materials for containment and cleaning up			
Methods for cleaning up	Take up liquid spill into absorbent material.		



Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

Other information

Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling	Do not soak in water or seawater. Do not expose to strong oxidizers. Do not give a strong mechanical shock or fling. Never disassemble, modify or deform. Do not connect the positive terminal to the negative terminal with electrically conductive material. Use only the chargers / electric tools specified by Hilti to charge or discharge the battery.	
Hygiene measures Additional hazards when processed	Do not throw into fire or expose to high temperatures (>85 °C). Do not connect the positive terminal to the negative terminal with electrically conductive material. Always wash hands after handling the product. Normal use of this product shall imply use in accordance with the instructions on the packaging and in line with the expectations of a professional user.	
7.2. Conditions for safe storage, including an	ny incompatibilities	
Storage conditions	Avoid direct sunlight, high temperature, high humidity. Store in a cool place (temperature: -20 °C ~ 40 °C, humidity: 45 - 85%).	
Storage area Incompatible products Incompatible materials Information on mixed storage	Store in a well-ventilated place. Strong bases. Strong acids. Sources of ignition. Direct sunlight. Store away from water. Do not store together with electrically conductive materials.	
Storage temperature	The accu-pack should be stored at 30 to 50% of the charging capacity. Avoid storing in places where it is exposed to static electricity. $-20 - 40$ °C	

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls	
Appropriate engineering controls	If the electrolyte is leaking out of the battery pack, the following measures have to be taken.
Other information	Do not eat, drink or smoke during use.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Avoid all unnecessary exposure.

Hand pr	otection
---------	----------

Wear protective gloves. Wear protective gloves.

Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12		EN ISO 374

Eye protection

Chemical goggles or safety glasses



Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

ern Baele prijelear and enernear prepertie	•
Physical state	Solid
Appearance	plastic case
Colour	red. Black.
Odour	odourless.
Odour threshold	Not available
Melting point	Not available
Freezing point	Not available
Boiling point	Not available
Flammability	Non flammable.
Lower explosion limit	Not applicable
Upper explosion limit	Not applicable
Flash point	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
рН	Not available
pH solution	Not available
Viscosity, kinematic (calculated value) (40 °C)	Not applicable
Partition coefficient n-octanol/water (Log Kow)	Not available
Vapour pressure	Not available
Vapour pressure at 50°C	Not available
Density	Not available
Relative density	Not available
Relative vapour density at 20°C	Not applicable
Solubility	Not available
Particle size	Not available

9.2. Data relevant with regard to physical hazard classes (supplemental)

Explosive properties

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Heating may cause a fire or explosion.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Water, humidity.

Risk of explosion by shock, friction, fire or other sources of ignition



Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

10.5. Incompatible materials

Conductive materials, water, seawater, strong oxidizers and strong acids.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects	11.1. Information on toxicological effects	
Acute toxicity (oral)	Not classified	
Acute toxicity (dermal)	Not classified	
Acute toxicity (inhalation)	Not classified	
Skin corrosion/irritation	Not classified	
Serious eye damage/irritation	Not classified	
Respiratory or skin sensitisation	Not classified	
Germ cell mutagenicity	Not classified	
Carcinogenicity	Not classified	
Reproductive toxicity	Not classified	
STOT-single exposure	Not classified	
STOT-repeated exposure	Not classified	
Aspiration hazard	Not classified	
Potential adverse human health effects and	This product contains an organic electrolyte. If the electrolyte is leaking out of the battery	
symptoms	pack, the following effects are known when getting into contact: Irritation: severely irritant to	
	eyes. Irritation: may cause irritation to the respiratory system.	
Other information	When used and handled according to specifications, the product does not have any harmful	
	effects according to our experience and the information provided to us.	

SECTION 12: Ecological information

12.1. Toxicity		
Hazardous to the aquatic environment, short-term	Not classified	
(acute)		
Hazardous to the aquatic environment, long-term	Not classified	
(chronic)		
12.2. Persistence and degradability		
Li-Ion Batteries <100 Wh		
Persistence and degradability	Not established.	
12.3. Bioaccumulative potential		
Li-Ion Batteries <100 Wh		
Bioaccumulative potential	Not established.	
12.4. Mobility in soil		
Li-Ion Batteries <100 Wh		
Mobility in soil	No additional information available	
12.5. Other adverse effects		
Ozone	Not classified	
Other adverse effects	No additional information available	
Other information	Do not allow battery packs to penetrate the soil.	
	The battery cell may corrode and electrolyte may leak.	



Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations

Dispose in a safe manner in accordance with local/national regulations. Refer to manufacturer/supplier for information on recovery/recycling. Avoid release to the environment.

Ecological information

n accordance with ADR / IMDG / IAT	A / RID /		
ADR	IMDG	ΙΑΤΑ	RID
14.1. UN number or ID number			
UN 3480	UN 3480	UN 3480	UN 3480
14.2. UN proper shipping nam	e		
LITHIUM ION BATTERIES	LITHIUM ION BATTERIES	Lithium ion batteries	LITHIUM ION BATTERIES
Transport document description			
UN 3480 LITHIUM ION BATTERIES, 9, (E)	UN 3480 LITHIUM ION BATTERIES, 9	UN 3480 Lithium ion batteries, 9	UN 3480 LITHIUM ION BATTERIES, 9
14.3. Transport hazard class(e	s)		
9	9	9	9
14.4. Packing group			· · · · · ·
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information availa	ble		
14.6. Special precautions for us	ser		
Overland transport			
Classification code (ADR)	M4		

Special provisions (ADR)	188, 230, 310, 348, 376, 377, 387, 636
Limited quantities (ADR)	0
Packing instructions (ADR)	P903, P908, P909, P910, P911, LP903, LP904, LP905, LP906
Transport category (ADR)	2
Tunnel restriction code (ADR)	E
Transport by sea	
Special provisions (IMDG)	188, 230, 310, 348, 376, 377, 384, 387
Limited quantities (IMDG)	0
Packing instructions (IMDG)	P903, P908, P909 , P910, P911, LP903, LP904, LP905, LP906
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-I
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW19



Product Safety Information Sheet

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis

MFAG-No	147
Air transport	
PCA packing instructions (IATA)	Forbidden
PCA max net quantity (IATA)	Forbidden
CAO packing instructions (IATA)	See 965
Special provisions (IATA)	A88, A99, A154, A164, A183, A201, A213, A331, A334, A802
Rail transport	
Special provisions (RID)	188, 230, 310, 348, _376, 377, 387, 636
Limited quantities (RID)	0
Packing instructions (RID)	P903, 908, 909, P910, P911, LP903, LP904, LP905, LP906

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary

basis <replaceemptycellby_no_relevan1_data></replaceemptycellby_no_relevan1_data>		
Issue date	11/11/2024	
Revision date	11/11/2024	
Supersedes	17/04/2024	

Section	Changed item	Change	Comments
1.1	Product name	Added	
3	Comments	Added	

SDS_UN_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.