

**Rotary hammer TE 2**



Drilling and Demolition

**Applications**

- Everyday hammer drilling in concrete, masonry and natural stone
- Occasional drilling in steel, wood and plastics using the optional chuck adaptor
- Driving screws using the optional bit holder
- Reverse rotation is useful for removing stuck drill bits
- Drilling in the 3-13 mm diameter range in solid metal / up to 20 mm in sheet metal
- Driving screws using the special bit holder

**Advantages**

- Dual-mode SDS rotary hammer (hammer drilling and drilling)
- Sturdy motor with high load rating for maximum reliability
- "TE-C Click" chuck and user-friendly selector switch for high working comfort
- Electronic switch for precise hole-starting
- 360° side handle adjusts easily for preference or for use in tight spaces
- Lock-on button for continuous fatigue-free use

**Technical data**

<b>Working mode</b>	Hammer drilling, Drilling only
<b>Optimum drilling diameter in concrete</b>	4 - 12 mm
<b>Drilling diameter range for hammer drill bits</b>	4 - 22 mm
<b>Single impact energy</b>	1.8 J
<b>Triaxial vibration value for hammer drilling into concrete (ah,HD)<sup>1)</sup></b>	13.5 m/s <sup>2</sup>
<b>A-weighted emission sound pressure level<sup>2)</sup></b>	91 dB (A)
<b>Dust removal module</b>	TE DRS-S (optional)
<b>Rated input power</b>	650 W
<b>Full hammering frequency</b>	4600 impacts/minute
<b>Dimensions (LxWxH)</b>	352 x 89 x 203 mm

<sup>1)</sup> according to EN 60745-2-6

<sup>2)</sup> according to EN 60745

<b>HILTI</b>	1 Year	<b>HILTI</b>
LIFETIME SERVICE	NO COSTS	FLEET MANAGEMENT
Lifetime	REPAIR COST LIMIT	
MANUFACTURER'S WARRANTY		



Ordering designation	Package contents	Sales pack quantity	Item number
TE 2	1x Rotary hammer TE 2 230V GB , 1x Case	1 pc	228091

Please visit our website for the latest item numbers and related products.